

Reebok

WORK SHOES

FE4 Adventure



ARTICLE IB3611

CATEGORY  S1 PS SR HRO FO

SIZES 36 - 47

WIDTH 11

WEIGHT
(half pair, sz 42) 460 GR

METAL FREE Yes

CERTIFICATION 

UPPER

Microfiber, Mesh and TPU

LINING

Microfiber. It gives a higher comfort during the whole working day. Optimal resistance to abrasion. High breathability

TOE CAP

XTR® Extra-wide Composite toe cap

ANTI-PERFORATION INSERT

Non-magnetic anti-perforation made of composite materials, 40% lighter and more flexible than a steel blade. It gives a major protection by covering the entire surface of the foot

FOOTBED

Molded Polyurethane Foam Cushion
Removable Footbed

OUTSOLE

Floatride Energy Midsole with Lugged SR Rubber Outsole and Toe Bumper

Requirements EN ISO 20345:2022 Test results

UPPER

Water Vapour Permeability	mg/cmq*h	≥ 0,8	52,5
Water Vapour Coefficient	mg/cmq	≥ 15	420,4

LINING

Water Vapour Permeability	mg/cmq*h	≥ 2,0	67,9
Water Vapour Coefficient	mg/cmq	≥ 20	543,2

TOE CAP

Impact resistance: clearance under the toecap	mm	≥ 14,0	19,5
Compression resistance: clearance under the toecap	mm	≥ 14,0	24,5

ANTI-PERFORATION INSERT

Penetration resistance (EN ISO 12568:2010)	N	≥ 1.000	≥ 1.000
--	---	---------	---------

ELECTRICAL RESISTANCE

wet condition (85% relative humidity)	MΩ	≥ 0,1	0,89
dry condition (30% relative humidity)	MΩ	≤ 1000	62,6

OUTSOLE

Abrasion resistance: relative volume loss	mm³	≤ 150	120,9
Flexing resistance: cut growth	mm	≤ 4	0,5
Resistance to fuel oil: volume increase	%	≤ 12	2,66
Energy absorption of seat region	J	≥ 20	31
Slip resistance on	Condition A	≥ 0,31	0,46
ceramic tile with sodium lauryl sulphate	Condition B	≥ 0,36	0,42
Slip resistance on	Condition C	≥ 0,19	0,25
ceramic tile with glycerine	Condition D	≥ 0,22	0,24

sheet version 1.2



MANUFACTURED BY WARSON BRANDS USA