

# Reebok

## WORK SHOES

### SPEED TR



**ARTICLE** IB4450

**CATEGORY**  S3S SR FO

**SIZES** 36 - 47

**WIDTH** 11

**WEIGHT**  
(half pair, sz 42) 450 GR

**METAL FREE** Yes

**CERTIFICATION** 

#### UPPER

Mesh with TPU

#### LINING

Breathable Moisture Wicking Mesh. It gives a higher comfort during the whole working day. Optimal resistance to abrasion

#### TOE CAP

COMPOSITE TOE CAP - Reduces weight while maintaining impact protection

#### ANTI-PERFORATION INSERT

Non-magnetic anti-perforation made of composite materials, 40% lighter and more flexible than a steel blade. It gives a major protection by covering the entire surface of the foot

#### FOOTBED

MemoryTech Memory Foam Removable Cushion Footbed

#### OUTSOLE

Dual Density Slip Resistant Rubber Bottom with RopePro Traction, TPU Stability Zone

#### UPPER

Water Vapour Permeability

**Requirements**  
**EN ISO 20345:2022**

**Test results**

mg/cmq\*h  $\geq 0,8$  1,5

Water Vapour Coefficient

mg/cmq  $\geq 15$  22,3

#### LINING

Water Vapour Permeability

mg/cmq\*h  $\geq 2,0$  67,9

Water Vapour Coefficient

mg/cmq  $\geq 20$  543,2

#### TOE CAP

Impact resistance: clearance under the toecap

mm  $\geq 14,0$  19,5

Compression resistance: clearance under the toecap

mm  $\geq 14,0$  24,5

#### ANTI-PERFORATION INSERT

Penetration resistance (EN ISO 12568:2010)

N  $\geq 1.000$   $\geq 1.000$

#### ELECTRICAL RESISTANCE

wet condition (85% relative humidity)

M $\Omega$   $\geq 0,1$  31,1

dry condition (30% relative humidity)

M $\Omega$   $\leq 1000$  125,4

#### OUTSOLE

Abrasion resistance: relative volume loss

mm<sup>3</sup>  $\leq 250$  99,7

Flexing resistance: cut growth

mm  $\leq 4$  0,2

Resistance to fuel oil: volume increase

%  $\leq 12$  8,36

Energy absorption of seat region

J  $\geq 20$  21

Slip resistance on

Condition A  $\geq 0,31$  0,60

ceramic tile with sodium lauryl sulphate

Condition B  $\geq 0,36$  0,43

Slip resistance on

Condition C  $\geq 0,19$  0,22

ceramic tile with glycerine

Condition D  $\geq 0,22$  0,24

sheet version 1.2



MANUFACTURED BY WARSON BRANDS USA